



Hyundai UMC, UTH



Styczniki i Przełączniki - HYUNDAI



Importer:

Mamy Moc!
Zenex
-P. P. H. U.-

 **HYUNDAI**
HEAVY INDUSTRIES CO.,LTD.

Przekładniki termiczne - Tabela specyfikacji

Model	UTH12	UTH32	UTH65	UTH100	UTH150	UTH265	UTH400	UTH800
Nastawa prądowa (A)	0.12-0.15-0.18 0.18-0.22-0.26 0.25-0.3-0.35 0.34-0.42-0.5 0.5-0.6-0.7 0.6-0.75-0.9 0.8-1-1.2 1.1-1.35-1.6 1.5-1.8-2.1 2-2.5-3 2.8-3.5-4.2 3-4-5 4-5-6 5.6-6.8-8 6-7.5-9 8-10-12	0.12-0.15-0.18 0.18-0.22-0.26 0.25-0.3-0.35 0.34-0.42-0.5 0.5-0.6-0.7 0.6-0.75-0.9 0.8-1-1.2 1.1-1.35-1.6 1.5-1.8-2.1 2-2.5-3 2.8-3.5-4.2 3-4-5 4-5-6 5.6-6.8-8 6-7.5-9 8-10-12 12-15-18 15-18.5-22 17-21-25 22-27-32	7-8.5-10 8-10-12 12-15-18 15-18.5-22 17-21-25 22-27-32 28-34-40 34-42-50 45-55-65	17-21-25 22-27-32 28-34-40 34-42-50 45-55-65 52-63-75 59-72-85 70-85-100	48-64-80 69-92-115 78-104-130 90-120-150	48-64-80 69-92-115 78-104-130 90-120-150 111-148-185 135-180-225 159-212-265	90-120-150 111-148-185 135-180-225 159-212-265 180-240-300 240-320-400	300-400-500 378-504-630 480-640-800
Styki pomocnicze	1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC
Wymiary (WxHxD, mm)	45x79x76	45x81x91	55x94x105	70x108x123	180x159x187	180x185x185	180x205x185	500A: 180x205x185 630A: 245x223x197 800A: 245x223x197
Zastosowanie z produktami	UMC9 UMC12	UMC18 UMC25 UMC32	UMC40 UMC50 UMC65	UMC75 UMC85 UMC100	UMC115 UMC130 UMC150	UMC185 UMC225 UMC265	UMC300 UMC400	UMC500 UMC630 UMC800
Adapter - montaż na szynie DIN	UTHMB12	UTHMB32	UTHMB65	UTHMB100	-	-	-	-

◆ Dobór referencji

UTH		12		K		A0100				S			
Symbol	Seria	Kod	Zastosowanie z produktami	Kod	Bimetale	Symbol	Nastawa prądu (A)	Symbol	Nastawa prądu (A)	Symbol	Nastawa prądu (A)	Kod	Akcesoria
UTH	UTH	12	UMC9-12	K	3	A0P18	0.12-0.18	A0009	6-9	A0080	48-80	S	Osłona bezpieczeństwa
		32	UMC18-32	H	2	A0P26	0.18-0.26	A0010	7-10	A0115	69-115		
		65	UMC40-65			A0P35	0.25-0.35	A0012	8-12	A0130	78-130		
		100	UMC75-100			A0P50	0.34-0.5	A0018	12-18	A0150	90-150		
UTH	UTH	150	UMC115-150			A0P70	0.5-0.7	A0022	15-22	A0185	111-185		
		265	UMC185-265			A0P90	0.6-0.9	A0025	17-25	A0225	135-225		
		400	UMC300-500			A1P20	0.8-1.2	A0032	22-32	A0265	159-265		
		800	UMC630-800			A1P60	1.1-1.6	A0040	28-40	A0300	180-300		
						A2P10	1.5-2.1	A0050	34-50	A0400	240-400		
						A0003	2-3	A0065	45-65	A0500	300-500		
						A4P20	2.8-4.2	A0075	52-75	A0630	378-630		
						A0005	3-5	A0085	59-85	A0800	480-800		
				A0006	4-6	A0100	70-100						
				A0008	5.6-8								

◆ Standardowe referencje - przykład

Model	Symbol	Status	Grupa towarowa
UTH12	UTH12K A0P50S	M	12
UTH32	UTH32K A0018S	M	
UTH100	UTH65K A0075S	M	
UTH265	UTH265K A0265S	M	

